

1. Unique identification code of the product-type: **MEG F1 thickness $\geq 2,0$ mm**
2. Uses: **HPL laminate used as external wall and ceiling finishes**
3. Manufacturer: **ABET LAMINATI spa - Viale Industria, 21 - 12042 BRA (CN) - Italy**
Tel. +39 0172 419 111 - Email: info@abetlaminati.com
4. System of AVCP: **system 1 – system 3**
5. Harmonised standard: **EN 438-7: 2005**
6. Notify Body: **CSI SpA - n° 0497**
7. Declared performance

Essential characteristics	Performance		
Reaction to fire	B-s1,d0 thickness ≥ 6 mm Mechanically fixed on metal frame D-s2,d0 2 mm \leq thickness < 6 mm Mechanically fixed on metal frame		
Resistance to fire	NPD		
Water vapour permeability	NPD		
Resistance to fixings	250 N (2 mm) 1000 N (4 mm)	2000 N (6 m) 3000 N (8 mm)	4000 N (≥ 10 mm)
Direct airborne sound insulation	NPD		
Flexural tensile strength	PASS		
Thermal resistance/conductivity	NPD		
Thermal shock resistance	PASS		
Release of formaldehyde	Class E1		
Durability Resistance to wet conditions Density	PASS ≥ 1350 kg/m ³		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Bra, 06/10/25

Simone Abrate
Simone Abrate
Technical Director